


# DDR5 Memory Modules

DDR5 is designed to meet increasing needs for efficient performance in a wide range of applications including cloud computing, and data center processing. The DDR5 memory provides developers with twice the performance (4800 to 6400 MT/s) and improved power efficiency in comparison to DDR4 by using an on-DIMM 12V voltage regulator (PMIC) and 1.1 I/O Voltage.

DDR5 also improves scaling performance without degrading channel efficiency at higher speeds. This increased performance is achieved by doubling the burst length to BL16 and bank-count from 16 to 32. For increased reliability and efficiency, a DDR5 DIMM utilizes two 40-bit fully independent sub-channels on the same module. DDR5 memory modules have a maximum die density of 64Gb and hence are capable of having a much higher DIMM storage capacity.

## Features

- Command/Address and Control bus is double data rate
- Generates CRC checksum in READ data frames
- Default burst length increased to BL16 – Single burst = 64B of data
- Integrated Temperature Sensor (MR4)
- DDR5 DRAM contain 256 mode registers



## Applications

- High Performance Computing
- Cloud Computing and Storage
- Enterprise Networking

## Benefits

- Higher Bandwidth
- Lower Power
- Better power efficiency and scalability
- Higher memory efficiency, lower latency
- Higher capacity DIMMs

## DDR5 Ordering Information

288-PIN - DDR5 RDIMM							
SMART Part Number	Density	Height (mm)	Module Config	Device Config	Speed	Voltage	Temp*
SR4G8RD5285SB	32GB	31.25	4Gb x80	2Gx8	4800MT/s	1.1V	0°C to +70°C

\* Reflects Operating Ambient Temperature

## DDR5 Ordering Information

288-PIN - DDR5 VLP RDIMM							
SMART Part Number	Density	Height (mm)	Module Config	Comp Config	Speed	Voltage	Temp*
SR6G8RD5388HMV	48GB	18.75	4Gb x80	3Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G8RD5288HAV	32GB	18.75	4Gb x80	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G8RD5288SBV	32GB	18.75	4Gb x80	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G8RD5288MDV	32GB	18.75	4Gb x80	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G8RD5285SBV	32GB	18.75	4Gb x80	2Gx8	4800MT/s	1.1V	0°C to +70°C
SR4G8RD5285HAV	32GB	18.75	4Gb x80	2Gx8	4800MT/s	1.1V	0°C to +70°C
262-PIN - DDR5 Non-ECC SODIMM							
SMART Part Number	Density	Height (mm)	Module Config	Comp Config	Speed	Voltage	Temp*
SR6G6SO5385HM	48GB	30.00	6Gb x64	3Gx8	4800MT/s	1.1V	0°C to +70°C
SRI4G6SO5288-SP	32GB	30.00	4Gb x64	2Gx8	5600MT/s	1.1V	-40°C to +85°C
SR4G6SO5288SB	32GB	30.00	4Gb x64	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G6SO5285SB	32GB	30.00	4Gb x64	2Gx8	4800MT/s	1.1V	0°C to +70°C
SR3G6SO5385HM	24GB	30.00	3Gb x64	3Gx8	4800MT/s	1.1V	0°C to +70°C
SRI2G6SO5288-SP	16GB	30.00	2Gb x64	2Gx8	5600MT/s	1.1V	-40°C to +85°C
SR2G6SO5288SB	16GB	30.00	2Gb x64	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR2G6SO5285SB	16GB	30.00	2Gb x64	2Gx8	4800MT/s	1.1V	0°C to +70°C
SRI1G6SO5168-SP	8GB	30.00	1Gb x64	1Gx16	5600MT/s	1.1V	-40°C to +85°C
262-PIN - DDR5 ECC SODIMM							
SMART Part Number	Density	Height (mm)	Module Config	Comp Config	Speed	Voltage	Temp*
SR8G7SO5488SM	64GB	30.00	8Gb x72	4Gx8	5600MT/s	1.1V	0°C to +70°C
SRI6G7SO5388HM	48GB	30.00	6Gb x72	3Gx8	5600MT/s	1.1V	-40°C to +85°C
SR6G7SO5388HM	48GB	30.00	6Gb x72	3Gx8	5600MT/s	1.1V	0°C to +70°C
SR6G7SO5385HM	48GB	30.00	6Gb x72	3Gx8	4800MT/s	1.1V	0°C to +70°C
SR4G7SO5288SB	32GB	30.00	4Gb x72	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G7SO5288HA	32GB	30.00	4Gb x72	2Gx8	5600MT/s	1.1V	0°C to +70°C
ST4G7SO5285SB	32GB	30.00	4Gb x72	2Gx8	4800MT/s	1.1V	0°C to +70°C
SRI4G7SO5285SB	32GB	30.00	4Gb x72	2Gx8	4800MT/s	1.1V	-40°C to +85°C
SR4G7SO5285SB	32GB	30.00	4Gb x72	2Gx8	4800MT/s	1.1V	0°C to +70°C
SRI2G7SO5288HA	16GB	30.00	2Gb x72	2Gx8	5600MT/s	1.1V	-40°C to +85°C
SR2G7SO5288SB	16GB	30.00	2Gb x72	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR2G7SO5288HA	16GB	30.00	2Gb x72	2Gx8	5600MT/s	1.1V	0°C to +70°C
SRI2G7SO5285SB	16GB	30.00	2Gb x72	2Gx8	4800MT/s	1.1V	-40°C to +85°C
SR2G7SO5285SB	16GB	30.00	2Gb x72	2Gx8	4800MT/s	1.1V	0°C to +70°C
288-PIN - DDR5 ECC UDIMM							
SMART Part Number	Density	Height (mm)	Module Config	Comp Config	Speed	Voltage	Temp*
SR6G7UD5388HM	48GB	31.25	6Gb x72	3Gx8	5600MT/s	1.1V	0°C to +70°C
SRI6G7UD5385MB	48GB	31.25	6Gb x72	3Gx8	4800MT/s	1.1V	-40°C to +85°C
SRI6G7UD5385HM	48GB	31.25	6Gb x72	3Gx8	4800MT/s	1.1V	-40°C to +85°C
SR6G7UD5385MB	48GB	31.25	6Gb x72	3Gx8	4800MT/s	1.1V	0°C to +70°C
SR6G7UD5385HM	48GB	31.25	6Gb x72	3Gx8	4800MT/s	1.1V	0°C to +70°C
SR4G7UD5288SB	32GB	31.25	4Gb x72	2Gx8	5600MT/s	1.1V	0°C to +70°C
SRI4G7UD5285SB	32GB	31.25	4Gb x72	2Gx8	4800MT/s	1.1V	-40°C to +85°C
SR4G7UD5285SB	32GB	31.25	4Gb x72	2Gx8	4800MT/s	1.1V	0°C to +70°C
SR2G7UD5288SB	16GB	31.25	2Gb x72	2Gx8	5600MT/s	1.1V	0°C to +70°C
SRI2G7UD5285SB	16GB	31.25	2Gb x72	2Gx8	4800MT/s	1.1V	-40°C to +85°C
SR2G7UD5285SB	16GB	31.25	2Gb x72	2Gx8	4800MT/s	1.1V	0°C to +70°C

\* Reflects Operating Ambient Temperature

## DDR5 Ordering Information

288-PIN - DDR5 ECC VLP UDIMM							
SMART Part Number	Density	Height (mm)	Module Config	Comp Config	Speed	Voltage	Temp*
SR8G7UD5488SMV	64GB	18.75	8Gb x72	4Gx8	5600MT/s	1.1V	0°C to +70°C
SR6G7UD5388HMV	48GB	18.75	6Gb x72	3Gx8	5600MT/s	1.1V	0°C to +70°C
SR6G7UD5385HMV	48GB	18.75	6Gb x72	3Gx8	4800MT/s	1.1V	0°C to +70°C
SR4G7UD5288SBV	32GB	18.75	4Gb x72	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G7UD5288MDV	32GB	18.75	4Gb x72	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G7UD5288HAV	32GB	18.75	4Gb x72	2Gx8	5600MT/s	1.1V	0°C to +70°C
SRI4G7UD5285SBV	32GB	18.75	4Gb x72	2Gx8	4800MT/s	1.1V	-40°C to +85°C
SR4G7UD5285SBV	32GB	18.75	4Gb x72	2Gx8	4800MT/s	1.1V	0°C to +70°C
SR2G7UD5288SBV	16GB	18.75	2Gb x72	2Gx8	5600MT/s	1.1V	0°C to +70°C
SRI2G7UD5285SBV	16GB	18.75	2Gb x72	2Gx8	4800MT/s	1.1V	-40°C to +85°C
SR2G7UD5285SBV	16GB	18.75	2Gb x72	2Gx8	4800MT/s	1.1V	0°C to +70°C

\* Reflects Operating Ambient Temperature



For more information, please visit: [www.smartm.com](http://www.smartm.com)

\*Product images are for promotional purposes only. Labels may not be representative of the actual product.

### Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231

F: (+1) 510-623-1434 • E: [info@smartm.com](mailto:info@smartm.com)

### Latin America:

T: (+55) 11 4417-7200 • E: [sales.br@smartm.com](mailto:sales.br@smartm.com)

### Asia/Pacific:

T: (+65) 6678-7670 • E: [sales.asia@smartm.com](mailto:sales.asia@smartm.com)

### EMEA:

T: (+44) 0 7826-064-745 • E: [sales.euro@smartm.com](mailto:sales.euro@smartm.com)

### Customer Service:

T: (+1) 510-623-1231 • E: [customers@smartm.com](mailto:customers@smartm.com)