



## ME2 | SATA | Slim SATA SSD

SMART's ME2 Slim SATA SSDs incorporate the latest generation 3D NAND-technology and SMART Modular's proprietary NVMSentry™ firmware to deliver high performance SSD products with endurance up to one drive writes per day (1 DDPD) for five years. The new ME2 SSDs offer better cost per bit over previous 64-layer and 96-layer NAND generations without sacrificing performance and reliability. Further optimization of the NVMSentry firmware also yields enhancements in read and write consistency over wide ranges of application workloads.



### Features & Benefits

- The Latest Generation 3D NAND Technology
- Quality of Service (QoS) with 3 Nines of Latency Consistency
- 1 DDPD For Five Years
- SEU Mitigation
- SMART's Proprietary NVMSentry Firmware
- TCG OPAL 2.0 and AES 256 Encryption
- End-to-End Data Path Protection
- Support I-Temp (-40°C to +85°C)

### Applications

- Automotive
- Chemical Plants
- Industrial
- Medical
- Oil Refinery
- Transportation

### Product Family Overview

Form Factor	Capacity	Sequential Performance
2.5" SSD	240GB to 1920GB	
M.2 2242 SSD	240GB to 960GB	
M.2 2280 SSD	240GB to 1920GB	Up to 540MB/s Read
mSATA SSD	240GB to 1920GB	Up to 460MB/s Write
Slim SATA SSD	240GB to 1920GB	

## Specifications

ME2   SATA   Slim SATA SSD	
NAND Type	eTLC
<b>Performance</b>	
Host Interface Rate (maximum)	SATA 3.0 6Gb/s
Capacities	240GB to 1920GB
Sequential Read (maximum)	Up to 540 MB/s
Sequential Write (maximum)	Up to 460 MB/s
Random Read (maximum)	Up to 77K IOPS
Random Write (maximum)	Up to 70K IOPS
<b>Reliability</b>	
MTBF	> 2,000,000 hours
Endurance (JEDEC Enterprise Workload) <sup>1</sup>	1920GB: 3755 TBW 960GB: 2275 TBW 480GB: 1015 TBW 240GB: 510 TBW
DWPD	1
SafeDATA	-
Error Correction	LDPC
<b>Data Security</b>	
Encryption	AES-256, TCG OPAL 2.0
<b>Power</b>	
Input Voltage	VCC: 5 V ± 10%
<b>Environmental</b>	
Shock	1500 g half-sine, 0.5 msec, 1 shock along each axis, X, Y, Z in each direction
Vibration	20G rms 80-2000Hz, 1.52mm 20-80Hz, 3 axis
Operating Temperature	Commercial: 0°C to +70°C Industrial: -40°C to +85°C
Storage Temperature	-40°C to +85°C
Humidity	40°C, Operation: 90% RH, Storage: 93% RH
<b>Physical</b>	
Length	39.00 mm
Width	54.00 mm
Height	4.00 mm

<sup>1</sup>Endurance is directly related to the User Specific Workload.

## Ordering Information

Part Number	Density
<b>ME2   SATA   Slim SATA SSD Commercial Operating Temperature (0°C to +70°C)</b>	
SRSLM1920FCM2AC4	1920GB
SRSLM960GFCM2AC4	960GB
SRSLM480GFCM2AC4	480GB
SRSLM240GFCM2AC4	240GB
<b>ME2   SATA   Slim SATA SSD Industrial Operating Temperature (-40°C to +85°C)</b>	
SRSLM1920FIM2AC4	1920GB
SRSLM960GFIM2AC4	960GB
SRSLM480GFIM2AC4	480GB
SRSLM240GFIM2AC4	240GB
<b>ME2   SATA   Slim SATA SSD (SEU Mitigation) Commercial Operating Temperature (0°C to +70°C)</b>	
SRSLM1920FCM2BC4	1920GB
SRSLM960GFCM2BC4	960GB
SRSLM480GFCM2BC4	480GB
SRSLM240GFCM2BC4	240GB
<b>ME2   SATA   Slim SATA SSD (SEU Mitigation) Industrial Operating Temperature (-40°C to +85°C)</b>	
SRSLM1920FIM2BC4	1920GB
SRSLM960GFIM2BC4	960GB
SRSLM480GFIM2BC4	480GB
SRSLM240GFIM2BC4	240GB



For more information, please visit: [www.smartm.com](http://www.smartm.com)

*\*Product images are for promotional purposes only. Labels may not be representative of the actual product.*

### Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231  
F: (+1) 510-623-1434 • E: [info@smartm.com](mailto:info@smartm.com)

### Latin America:

T: (+55) 11 4417-7200 • E: [sales.br@smartm.com](mailto:sales.br@smartm.com)

### Asia/Pacific:

T: (+65) 6678-7670 • E: [sales.asia@smartm.com](mailto:sales.asia@smartm.com)

### EMEA:

T: (+44) 0 7826-064-745 • E: [sales.euro@smartm.com](mailto:sales.euro@smartm.com)

### Customer Service:

T: (+1) 510-623-1231 • E: [customers@smartm.com](mailto:customers@smartm.com)