



H9 | CF 6.1 | CF Card

SMART's H9 CF Cards offer reliable, high performance in an industry standard CompactFlash® (CF) form factor. The industrial-grade H9 CF Card products specifically support OEM markets of networking, telecommunication and data communication, embedded computing, medical, and industrial applications. SMART has designed their CF Cards using Single-Level Cell (SLC) Flash technology for enhanced data integrity and life time expectations in critical embedded applications.

SMART's CF Card product line supports Self-Monitoring Analysis and Reporting Technology (S.M.A.R.T.), which is designed to reduce field failures and unscheduled service maintenance. S.M.A.R.T. enables a reliable monitoring application that efficiently supports CF Cards in the field and guarantees 24/7 service availability.



Features & Benefits

- Highly Reliable SLC NAND Flash Technology
- Static and Dynamic Wear-Leveling
- Field Upgradeable Firmware
- RoHS-6 Compliant
- Self-Monitoring Analysis and Reporting Technology (S.M.A.R.T.) Support

Applications

- Communications
- Defense
- Gaming
- Industrial Control Equipment
- Networking
- Printers

Product Family Overview

Form Factor	Capacity	Sequential Performance
CF 6.1 CF Card	64MB to 64GB	Up to 103MB/s Read Up to 73MB/s Write

Specifications

H9 CF 6.1 CF Card	
NAND Type	SLC
Performance	
Sequential Read (maximum)	Up to 103MB/s
Sequential Write (maximum)	Up to 73MB/s
Reliability	
Data Reliability	< 1 Non-Recoverable Error in 10 ¹⁴ bits read
Data Retention	10 years >90% life remaining 1 year at the end of life
Endurance	TBW up to 5TB per 1GB capacity
Power	
VCC	5.0V+10% 3.3V+5%
Read	< 200mA
Write	< 200mA
Idle	< 4mA
Environmental	
Shock (operational)	50G @ 11ms
Vibration	15G peak to peak
Operating Temperature	Commercial: 0°C to +70°C Industrial: -40°C to +85°C
Storage Temperature	-55°C to +85°C
Humidity	5% to 95%
Physical	
Length	36.4mm
Width	42.8mm
Thickness	3.3mm

Ordering Information

Part Number	Density
H9 CF 6.1 CF Card	
Commercial Operating Temperature (0°C to +70°C)	
SP9FD64GH9UES01	64GB
SP9FD32GH9UDS01	32GB
SP9FD16GH9UCS01	16GB
SP9FD08GH9UBS01	8GB
SP9FD04GH9UAS01	4GB
SP9FD02GH9US01	2GB
SP9FD01GH9U4S01	1GB
SP9FD512H9U2S01	512MB
SP9FD256H9U1S01	256MB
SP9FD128H9U1S01	128MB
SP9FD064H9U1S01	64MB
H9 CF 6.1 CF Card	
Industrial Operating Temperature (-40°C to +85°C)	
SP9FD64GH9UEIS01	64GB
SP9FD32GH9UDIS01	32GB
SP9FD16GH9UCIS01	16GB
SP9FD08GH9UBIS01	8GB
SP9FD04GH9UAIS01	4GB
SP9FD02GH9UIS01	2GB
SP9FD01GH9U4IS01	1GB
SP9FD512H9U2IS01	512MB
SP9FD256H9U1IS01	256MB
SP9FD128H9U1IS01	128MB
SP9FD064H9U1IS01	64MB



For more information, please visit: www.smartm.com

*Product images are for promotional purposes only. Labels may not be representative of the actual product.

Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231
F: (+1) 510-623-1434 • E: info@smartm.com

Latin America:

T: (+55) 11 4417-7200 • E: sales.br@smartm.com

Asia/Pacific:

T: (+65) 6678-7670 • E: sales.asia@smartm.com

EMEA:

T: (+44) 0 7826-064-745 • E: sales.euro@smartm.com

Customer Service:

T: (+1) 510-623-1231 • E: customers@smartm.com