



RD130m | SD 3.01 | microSD Card

SMART's RD130m microSD Cards are fully SD compliant. Offered in commercial and industrial temperature versions based on 32nm and 24nm SLC Flash technologies, the RD130m microSD Cards are specifically designed to meet strict industrial operating and environmental requirements.

SMART's RD130m microSD Cards comply with SD v3.01 Standard with performance up to 68MB/s read and 50MB/s write. Incorporating onboard error detection and correction algorithms, and static and dynamic wear-leveling techniques, SMART's microSD Memory Cards ensure years of reliable operation over a product's life.



Features & Benefits

- Capacities:
 - 4GB (SDHC)
 - 1GB, 2GB (SDSC)
- SLC NAND Flash
- Low Power Dissipation
- Onboard Wear-Leveling
- RoHS Compliant

Applications

- Embedded Computing
- Industrial Meters and Industrial Control
- Medical Equipment
- Networking
- Telecom and Communications

Product Family Overview

Form Factor	Capacity	Sequential Performance
SD 3.01 microSD Card (SDHC)	4GB	Up to 68MB/s Read Up to 50MB/s Write
SD 3.01 microSD Card (SDSC)	1GB, 2GB	Up to 23MB/s Read Up to 22MB/s Write

Specifications

RD130m SD 3.01 microSD Card	
NAND Type	SLC
Performance	
Sequential Read (maximum)	SD 3.01
Sequential Read (maximum)	Up to 68MB/s (4GB) Up to 23MB/s (1GB, 2GB)
Sequential Write (maximum)	Up to 50MB/s (4GB) Up to 22MB/s (1GB, 2GB)
Reliability	
MTBF	> 3,000,000
Endurance (Sequential Workload) ¹	4GB: 234TBW 2GB: 117TBW 1GB: 58TBW
Power	
Vcc	2.7 - 3.6 V
Environmental	
Operating Temperature	Extended: -25°C to +85°C Industrial: -40°C to +85°C
Storage Temperature	-40°C to +85°C
Humidity	25% to 95%
Physical	
Length	15 mm
Width	11 mm
Height	0.7/1.0 mm

¹Endurance is directly related to 128k sequential write workload

Ordering Information

Part Number	Density
RD130m SD 3.01 microSD Card Extended Operating Temperature (-25°C to +85°C)	
SS9UD004GPHE8SE32	4GB
SS9UD002GPHE8SE32	2GB
SS9UD001GPHE8SE32	1GB
RD130m SD 3.01 microSD Card Industrial Operating Temperature (-40°C to +85°C)	
SS9UD004GPHE8SI32	4GB
SS9UD002GPHE8SI32	2GB
SS9UD001GPHE8SI32	1GB



For more information, please visit: www.smartm.com

**Product images are for promotional purposes only. Labels may not be representative of the actual product.*

Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231
F: (+1) 510-623-1434 • E: info@smartm.com

Latin America:

T: (+55) 11 4417-7200 • E: sales.br@smartm.com

Asia/Pacific:

T: (+65) 6678-7670 • E: sales.asia@smartm.com

EMEA:

T: (+44) 0 7826-064-745 • E: sales.euro@smartm.com

Customer Service:

T: (+1) 510-623-1231 • E: customers@smartm.com