



## DuraFlash™

# RD230 | SD 6.1 | SD Card

SMART's DuraFlash, high-capacity, RD230 SD Cards are fully SD UHS-I compliant. The RD230 SD Cards are offered in industrial temperature with capacities from 32GB to 256GB. They are specifically designed to meet strict environmental requirements as in networking, industrial, gaming and automotive applications.

Incorporating onboard error detection and correction algorithms and static and dynamic wear-leveling techniques, SMART's RD230 SD Cards ensure years of reliable operation over a product's life.



### Features & Benefits

- Capacities: 64GB to 256GB (SDXC), 32GB (SDHC)
- SD UHS-I Compliant
- Support I-Temp (-40°C to +85°C)
- Low Power Dissipation
- Onboard Wear-Leveling

### Applications

- Automotive
- Gaming
- Industrial
- Networking

### Product Family Overview

Capacity	Sequential Performance
<b>RD230   SD 6.1   SD Card</b>	
32GB to 256GB	Up to 95MB/s Read; Up to 55MB/s Write

# Specifications

RD230   SD 6.1   SD Card	
NAND Type	TLC
<b>Performance</b>	
Host Interface Rate (maximum)	SD 6.1 (SDR 104)
Capacities	32GB to 256GB
Sequential Read (maximum)	Up to 95MB/s
Sequential Write (maximum)	Up to 55MB/s
<b>Reliability</b>	
MTBF	> 3,000,000 hours
Data Reliability	< 1 Non-Recoverable Error in 10 <sup>17</sup> bits read
Data Retention	10 years >90% life remaining 1 year at the end of life
Endurance (Sequential Workload) <sup>1</sup>	256GB: 700 TBW 128GB: 350 TBW 64GB: 175 TBW 32GB: 87 TBW
<b>Environmental</b>	
Shock	1500 g half-sine, 0.5 msec, 1 shock along each axis, X, Y, Z in each direction
Vibration	20G 80-2000Hz, 1.52mm 20-80Hz, 3 axis
Operating Temperature	Industrial: -40°C to +85°C
Storage Temperature	-40°C to +85°C
Humidity	40°C, Operation: 90% RH, Storage: 93% RH
<b>Physical</b>	
Length	32.0mm
Width	24.0mm
Thickness	2.1mm

<sup>1</sup>Endurance is directly related to 128k sequential write workload.



For more information, please visit: [www.smartm.com](http://www.smartm.com)

*\*Product images are for promotional purposes only. Labels may not be representative of the actual product.*

#### Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231  
F: (+1) 510-623-1434 • E: [info@smartm.com](mailto:info@smartm.com)

#### Latin America:

T: (+55) 11 4417-7200 • E: [sales.br@smartm.com](mailto:sales.br@smartm.com)

#### Asia/Pacific:

T: (+65) 6678-7670 • E: [sales.asia@smartm.com](mailto:sales.asia@smartm.com)

#### EMEA:

T: (+44) 0 7826-064-745 • E: [sales.euro@smartm.com](mailto:sales.euro@smartm.com)

#### Customer Service:

T: (+1) 510-623-1231 • E: [customers@smartm.com](mailto:customers@smartm.com)