



# Liquid Immersion RDIMMs for Data Centers

Reliable, Trusted, Proven

## Why Liquid Immersion Servers?




- Power and heat, two of the biggest issues affecting data centers today
- Liquid cooling reduces power consumption by eliminating fans. Liquid cooling reduces space and removes overhead for cooling infrastructure

## Problems with using standard RDIMMs in Liquid Immersion Servers

- Potential failures caused by corrosion due to changes in physical and chemical properties of the PCB and electrical components
- Fading component markings – unable to identify components
- Module label degrades – unable to track modules

## Solutions

- Conformal coating - thin polymeric film which conforms to a printed circuit board to protect the board's components
- Typically applied at 25-250µm thickness, it is applied to electronic circuitry to protect against liquid, moisture, dust, and other corrosive chemicals such as sulfur dioxide
- SMART uses in-house, leading-edge equipment with a fully automated spray for applying conformal coating
- SMART uses high quality acrylic, polyurethane, silicone, epoxy coating material
- Designed to be highly reliable for use in Liquid Immersion Servers



Server boards being immersion cooled

## Applications

- Liquid Immersion Servers used in data centers

# DDR5 Liquid Immersion RDIMM Ordering Information

288-PIN - DDR5 RDIMM							
SMART Part Number	Density	Height (mm)	Module Config.	Device Type	Speed	Voltage	Temperature
SRLBG8RD544H-SB	256GB	31.25	32Gb x80	16Gx4	5600MT/s	1.1V	0°C to +70°C
SRLAG8RD5846-SB	128GB	31.25	16Gb x80	4Gx4	4800MT/s	1.1V	0°C to +70°C
SRLHG8RD5648-SP	96GB	31.25	12Gb x80	6Gx4	5600MT/s	1.1V	0°C to +70°C
SRL8G8RD5448-SP	32GB	31.25	4Gb x80	4Gx4	5600MT/s	1.1V	0°C to +70°C
SRL4G8RD5248-SP	32GB	31.25	4Gb x80	4Gx4	5600MT/s	1.1V	0°C to +70°C
SRL4G8RD5288-SP	32GB	31.25	4Gb x80	2Gx8	5600MT/s	1.1V	0°C to +70°C

\* Reflects Operating Ambient Temperature



For more information, please visit: [www.smartm.com](http://www.smartm.com)

*\*Product images are for promotional purposes only. Labels may not be representative of the actual product.*

**Headquarters/North America:**

T: (+1) 800-956-7627 • T: (+1) 510-623-1231  
F: (+1) 510-623-1434 • E: [info@smartm.com](mailto:info@smartm.com)

**Latin America:**

T: (+55) 11 4417-7200 • E: [sales.br@smartm.com](mailto:sales.br@smartm.com)

**Asia/Pacific:**

T: (+65) 6678-7670 • E: [sales.asia@smartm.com](mailto:sales.asia@smartm.com)

**EMEA:**

T: (+44) 0 7826-064-745 • E: [sales.euro@smartm.com](mailto:sales.euro@smartm.com)

**Customer Service:**

T: (+1) 510-623-1231 • E: [customers@smartm.com](mailto:customers@smartm.com)